



## TEMPO<sup>2</sup>: the new Silent Box<sup>®</sup>

**Silent Box<sup>®</sup>,**  
soundproof cabin  
for TEMPO lines.

- 75 dB(A) @ 1 mt in any direction
- Built-in electrical cabinet
- Complete accessibility for full maintenance
- In-out silenced air fan
- Easy and quick installation
- Available also for SIAD MI compressors already installed

 **SIAD** **MACCHINE  
IMPIANTI**

SIAD Macchine Impianti, Italy  
Tel. +39 035 327611  
Fax +39 035 316131  
info@siadmi.com  
www.siadmi.com

# TEMPO<sup>2</sup>: THE NEW MODELS 2008

TEMPO <sup>2</sup> model	Output (*)	Installed power [kW] [Hp]	Adsorbed power [kW] [Hp]	Specific consumption [kWh/m <sup>3</sup> ] [Hp/cfm]
	[Nm <sup>3</sup> /h] [Ncfm]			
TEMPO <sup>2</sup> 90	90	18	16	0,18
	53	24	22	0,41
TEMPO <sup>2</sup> 140	140	37	27	0,19
	82	50	37	0,44
TEMPO <sup>2</sup> 260	260	55	50	0,19
	153	75	68	0,44
TEMPO <sup>2</sup> 350	350	75	65	0,19
	206	102	88	0,44
TEMPO <sup>2</sup> 450	450	90	80	0,18
	265	122	109	0,41
TEMPO <sup>2</sup> 610	610	132	118	0,19
	359	180	160	0,44
TEMPO <sup>2</sup> 800	800	200	162	0,20
	471	272	220	0,47
TEMPO <sup>2</sup> 950	950	220	176	0,19
	559	299	239	0,44
TEMPO <sup>2</sup> 1100	1.100	220	195	0,18
	647	299	265	0,41
TEMPO <sup>2</sup> 1300	1.300	250	225	0,17
	765	340	306	0,39
TEMPO <sup>2</sup> 1500	1.500	315	265	0,18
	883	428	360	0,41
TEMPO <sup>2</sup> 1850	1.850	375	320	0,17
	1.089	510	435	0,39
TEMPO <sup>2</sup> 2100	2.100	400	365	0,17
	1.236	544	496	0,39
TEMPO <sup>2</sup> 2350	2.350	450	390	0,17
	1.383	612	530	0,39

TEMPO <sup>2</sup> model	Output (*)	Installed power [kW] [Hp]	Adsorbed power [kW] [Hp]	Specific consumption [kWh/m <sup>3</sup> ] [Hp/cfm]
	[Nm <sup>3</sup> /h] [Ncfm]			
TEMPO <sup>2</sup> 2600 (a)	2.600	500	450	0,17
	1.530	680	612	0,39
TEMPO <sup>2</sup> 3000 (a)	3.000	630	530	0,18
	1.766	857	721	0,41
TEMPO <sup>2</sup> 3700 (a)	3.700	750	640	0,17
	2.178	1.020	870	0,39
TEMPO <sup>2</sup> 4200 (a)	4.200	800	730	0,17
	2.472	1.088	992	0,39
TEMPO <sup>2</sup> 4700 (a)	4.700	900	780	0,17
	2.766	1.224	1.061	0,39
TEMPO <sup>2</sup> 5550 (b)	5.550	1.125	960	0,17
	3.267	1.530	1.306	0,39

**NB:** models TEMPO<sup>2</sup> 2600 through to TEMPO<sup>2</sup> 5550 are composed of two or three compressors arranged in parallel, to ensure maximum production flexibility.

(a) two parallel compressors

(b) three parallel compressors

(\*) with dry intake air at 0°C, at sea level

**These data are indicative only.** SIAD Macchine Impianti reserves the right to modify the technical specifications and features of its products without notice.